

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049740 A1

(51) International Patent Classification⁷: **C09D 11/00**

(21) International Application Number:
PCT/EP2004/012467

(22) International Filing Date:
4 November 2004 (04.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03025903.0 12 November 2003 (12.11.2003) EP

(71) Applicant (for all designated States except US): **SICPA HOLDING S.A.** [CH/CH]; Avenue de Florissant 41, CH-1008 Prilly (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TILLER, Thomas** [DE/CH]; Chemin du Cèdre 21, CH-1030 Bussigny (CH). **MARGUERETTAZ, Xavier** [CH/CH]; R. du Guercet 93, CH-1920 Martigny (CH).

(74) Agents: **HEPP, Dieter et al.**; Hepp Wenger Ryffel AG, Friedtalweg 5, CH-9500 Wil (CH).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.








(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **INKJET INK COMPOSITION EXHIBITING LOW GLOSS**



(57) Abstract: Non-visible ink-jet printing ink composition for marking a substrate, comprising at least one marking compound absorbing light outside the visible wavelength range of about 400 - 700 nm, and which comprises a hydrocarbon compound, having two to six carbon atoms carrying two or three hydroxyl groups, as a non-particulate matting agent, so as to adapt the gloss of the ink-jet printed marking to the gloss of the substrate.

WO 2005/049740 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.